

# MEEZAN DOT 4

BRAKE AND CLUTCH FLUID



## Performance Claims

MEETS REQUIREMENT OF: US FMVSS 116 DOT 4; SAE J1703; ISO 4925

## Product Description

Meezan DOT 4 is universal brake & clutch fluid manufactured from specialized synthetic components under strict conditions to produce a fluid with a very high operating temperature. Meezan DOT 4 is specially formulated for use in the majority of automotive applications, however it is recommended that the user should always check in the vehicle handbook before use.

## Features & Benefits

- #Suitable for use in all systems where a non-mineral based fluid is recommended.
- #Meets DOT 4 specifications for improved heavy braking performance.
- #Low moisture absorption by providing superior boiling point and high vapor lock.
- #Mixes with DOT 3 brake fluids.

## Applications

Meezan DOT 4 Brake Fluid, is suitable as a brake & clutch systems for cars, commercial vehicles and motorcycles.

**Caution:** Brake fluid can damage vehicle paintwork and it must be washed off with water immediately. It is also necessary to keep the container tightly sealed to prevent absorption of moisture. Contamination with dirt, water, petroleum products or other materials may result in brake failure repairs.

Typical Test Data			
Characteristics	Method	Unit	Typical Value
Product Name			DOT 4
Product Code			AF54000
Appearance	Visual	None	Transparent
Specific Gravity @15.6 °C	ASTM D 4052	Kg/ L	1.03
Dry Equilibrium Reflux Boiling Point	ASTM D 1120	°C	266
Wet Equilibrium Reflux Boiling	ASTM D 1120	°C	166
Point Kinematic Viscosity @ 100°C	ASTM D 7042	cSt	2.01
Kinematic Viscosity @ -40°C	ASTM D 7042	cSt	1400
PH	ASTM D 1287	None	8.24

## Health and Safety

This product used as our recommendation for intended application is not expected to produce any particular risk. A safety data sheet of the product is available on request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.